

RESPONSE  
SN 09/585,263  
PAGE - 2 of 11 -

RECEIVED  
CENTRAL FAX CENTER

NOV 15 2006

**LISTING OF THE CLAIMS**

Please consider the claims as follows:

1. (Previously presented) A method, comprising:  
generating, at a headend, at least one bitmap for a channel information window;  
encoding, at the headend, a broadcast video presentation and the bitmap for the channel information window, the broadcast video presentation being programming from one of a plurality of channels;  
transmitting, from the headend to a set top terminal, the broadcast video presentation and the bitmap for the channel information window;  
receiving, at the set top terminal, a signal to activate the channel information window;  
decoding, at the set top terminal, the broadcast video presentation and the bitmap for the channel information window; and  
compositing, at the set top terminal, the bitmap for the channel information window and the broadcast video presentation to produce a video stream for a display so that the channel information window overlays and obscures at least a portion of the broadcast video presentation on the display.
2. (Original) The method of claim 1, wherein transmitting the bitmap for the channel information window is performed via an out-of-band channel.
- 3-4. (Cancelled).
5. (Previously presented) A method, comprising:  
generating, at a headend, a plurality of bitmaps for each of a plurality of channel information windows;  
encoding, at the headend, a plurality of broadcast video displays and the channel information windows, the broadcast video displays including a particular broadcast

503785-1

**RESPONSE**

SN 09/585,263

PAGE - 3 of 11 -

video display, each broadcast video display being programming from one of a plurality of channels, the channel information windows including information about the channels;

transmitting, from the headend to the set top terminal, the broadcast video displays and the channel information windows;

decoding, at the set top terminal, the broadcast video displays and the channel information windows;

compositing, at the set top terminal, the particular broadcast video display and an associated one of the channel information windows to produce a video stream for a display so that the channel information window overlays and obscures at least a portion of the particular broadcast video display; and

changing, at the set top terminal, the channel information window in response to a navigation command, while the particular broadcast video display remains the same.

6. (Cancelled)

7. (Previously presented) The method of claim 5, further comprising:

changing the particular broadcast video display to a new broadcast video display, upon termination of the navigation command in that mode;

wherein changing the particular broadcast video display is accomplished by generating, encoding, and transmitting video packet streams at the headend.

8. (Previously presented) The method of claim 5, wherein the navigation command in that mode navigates only through favorite channels.

9. (Previously presented) A method, comprising:

generating, at a headend, a broadcast video presentation and at least one bitmap for a channel information window, the broadcast video presentation being programming from one of a plurality of channels;

encoding, at the headend, the broadcast video presentation and the bitmap for the channel information window;

## RESPONSE

SN 09/585,263

PAGE - 4 of 11 -

transmitting, from the headend to a terminal, the broadcast video presentation and the channel information window; and

sending, from the terminal to the headend, a signal to activate the channel information window;

wherein the bitmap for the channel information window is overlaid over the broadcast video presentation so that the channel information window obscures at least a portion of the broadcast video presentation.

10. (Previously presented) A method, comprising:

receiving, at a terminal from a headend, a broadcast video presentation, the broadcast video presentation being programming from one of a plurality of channels;

sending, to the headend from the terminal, a signal to activate a channel information window;

receiving, at the terminal from the headend, a bitmap for the channel information window;

decoding, at the terminal, the broadcast video presentation and the channel information window; and

compositing, at the terminal, the bitmap for the channel information window with the broadcast video presentation to produce a video stream for display so that the channel information window overlays and obscures at least a portion of the broadcast video presentation in the video stream.

11-12. (Cancelled)

13. (Previously presented) The method of claim 1, further comprising:

requesting, by the set top terminal from the headend, the bitmap for the channel information window in response to the signal to activate the channel information window.

RESPONSE  
SN 09/585,263  
PAGE - 5 of 11 -

14. (Previously presented) The method of claim 1, wherein the bitmap for the channel information window is broadcast continually and the set top terminal causes the channel information window to overlay the broadcast video presentation in response to the signal to activate the channel information window.

503785-1